

Y-C Fair Demolition Derby

IMPORT CLASS RULES

Remove all air bags, all glass, trim, antennas, headlights, taillights, rear seat, stripping, mirrors, license plates, carpets, door handles, plastic grills, and headliner.

1. Interior must be completely removed.
2. Windshield screen with two bars from roof to cowl, no more than 12" apart
3. Door bars cannot have sharp edges
4. 80's and newer front wheel drive, All wheel drive and rear wheel drive cars; 6 cylinders or less; 108-inch wheelbase maximum
5. Pad driver's door from top to bottom. Pad steering wheel for driver safety. Must use at least 1" padding.
6. Cars must be able to stop on at least one axle.
7. Trailer hitches must be removed.
8. Number Plate on top of car needs to be visible from the stands
9. Door and trunk must be chained closed with at least 3/8" chain.
10. Hood can have (2) 1" all-thread and/or be chained closed. The all-thread can be welded to the frame and go up through the hood, but no sharp edges
11. Hood will need two holes cut -144(12x12) square inches each
12. Trunk will need two holes cut -144(12x12) square inches each

Aftermarket parts allowed: Gas tank, shifter, driveline, battery box, SMALL distributor protector, steering column, intake manifolds, headers & gas pedal

Cage minimum: Rear seat bar with an upright connected to the roof or a halo bar with 10" x10" end plates (if not doing a box cage). Halo/upright MUST be attached to the roof and floor.

You may choose to add a dash bar, inside door side bars, & a gas tank protector. No larger than 6" tubing to the frame floor or unibody. No kickers of any kind.

Cars with crush boxes in front of the radiator core support may be removed.

Bumpers:

1. Original passenger car bumpers only. Must be OEM.

2. Bumpers MAY NOT be loaded. Maximum bumper height is 22" to the bottom of the bumper.
3. Weld your front bumper on existing brackets with no added fill and all other bumper brackets must be removed. Bumper brackets and shock tubes must be what came from the factory on the car.
4. Chaining bumper. 3/8" chain, two wraps around front and rear bumper. This is to prevent bumper from falling off.
5. No homemade pointy or Chrysler pointy bumpers.

Radiator:

1. Radiator must be run and in stock location. No added coolant or reservoirs or bypassing the radiator.

Gas tank:

1. May remain in stock position if it is located in front of the rear axle, okay to run minimum gas (2 gallons) or run a standard metal derby tank that is bolted in the back seat.

Battery:

1. MUST BE relocated to passenger seat floorboard
2. Battery must be in a battery box and bolted or strapped to the floor

Tires & Rims:

1. Must be DOT. No studded tires or skid steer tires.
2. Mud tires and grooving tires is allowed.
3. No snow chains or anything wrapped around tires for traction is allowed
4. Rims must be OEM steel rims. Valve stem protectors allowed

Automatic transmission dipsticks must be clamped / sealed closed

REAR WHEEL DRIVE

Stock rear end only. It is recommended the you weld the spider gears or install a posi.

Factory leaf springs that came on that car must be run with factory mounting and clamps. Do not alter what is on it.

One chain wrap from the rear frame to the rear end on RWD cars allowed.

Safety:

1. 4-point harness must be in good working order no burn marks or air weathered
2. DOT approved helmet

3. Long pants
4. Long sleeved shirt
5. Good working fire extinguisher located within drivers reach
6. No passengers
7. Neck brace recommended
8. Battery disconnect recommended
9. No open toe shoes

This is a chain and go demolition derby. Be safe and have fun.

Rules are subject to change.

Any questions, please call the Yamhill County Fair Office @ (503) 434-7524.

You can also reach out to us @ facebook.com/yamcodemoderby